

**FINANCIAL COMPARATIVE STATEMENT**  
**Establishment of Govt Technical & Vocational Centre in Rented Building & Procurement of Equipment / Machinery & Furniture at Maidan, Dir Lower Khyber Pakhtunkhwa**  
**DATE OF TENDER OPENING 28-04-2021**  
**(COMPUTER LAB EQUIPMENT)**

Item No.	Name of Items	QTY	AURSOF PVT (Ltd), Peshawar		ANS Associates, Lahore		Lowest	Remarks
			Models	Financial Quoted Rates	Models	Financial Quoted Rates		
1	<b>Processor: 10th Generation Intel® Core™ i5-10400</b> , 12 MB Cache, 6 Core, 12 Threads, 2.9 GHz to 4.3 GHz. Chipset: Intel B460 chipset or higher Memory: 8GB - DDR4, 2666MHz Hard Drive: 1TB 7200RPM 3.5" SATA HDD Optical Drive: 9.5 mm Slimline DVD +/- RW Graphics Card: Intel® UHD Graphics 630 with shared graphics memory or higher Communication: Gigabit Ethernet controller 10/100/1000 (RJ45) Ports: 2 USB 2.0(front), 2 USB 3.2 Gen 1 Type-A (front), 1 HDMI, 1 VGA 2 USB 3.2 Gen 1 Type-A (rear), 2 USB 2.0(rear), 1 RJ-45 Ethernet Wireless: Intel® Wireless-AC 3165 802.11ac 1x1 + Bluetooth 4.2 or higher Keyboard: USB Keyboard and Mouse Antivirus with 1 year subscription Display: 18.5" LED Warranty: 3-years Provision of Manufacturer / Distributor authorization letter in the name of undersigned is mandatory.	25	Dell Optiplex 3080	118,800	Vestro 3888	105,931	105,931	ANS Associates, Lahore
2	<b>MULTIFUNCTIONAL PRINTERS</b> Functions: PRINT/SCANNER/COPY/FAX	1	HP Laserjet Pro M-227FDW	83,000	HP Laserjet Pro MFP M-227fdn Printer	81,600	81,600	ANS Associates, Lahore
3	<b>MULTIMEDIA PROJECTOR with motorized Screen system.</b> Type of display Poly-silicon TFT active matrix Resolution BrightLink 480i: 1024 × 768 pixels (XGA) BrightLink 475Wi/485Wi: 1280 × 800 pixels (WXGA) Lens F= 1.80 Focal length: 3.71 mm Color reproduction Full color, 16.77 million colors Brightness BrightLink 475Wi: Normal Power Consumption mode: White light output 2600 lumens (ISO 21118 standard) Color light output 2600 lumens ECO Power Consumption mode: White light output 1800 lumens (ISO 21118 standard) BrightLink 480i: Normal Power Consumption mode: White light output 3000 lumens (ISO 21118 standard) Color light output 3000 lumens ECO Power Consumption mode: White light output 1800 lumens (ISO 21118 standard) BrightLink 485Wi: Normal Power Consumption mode: White light output 3100 lumens (ISO 21118 standard) Color light output 3100 lumens ECO Power Consumption mode: White light output 1800 lumens (ISO 21118 standard) Contrast ratio 3000 to 1 with Auto Iris on and Normal Power Consumption mode Image size BrightLink 480i: 55.9 to 93.2 inches (1.42 to 2.37 m) BrightLink 475Wi/485Wi: 60 to 100 inches (1.52 to 2.54 m) Projection distance 13.7 to 23.5 inches (0.35 to 0.60 m) Projection methods Front, wall or ceiling-mounted Optical aspect ratio (width-to-height) BrightLink 480i: 4:3 BrightLink 475Wi/485Wi: 16:10 Focus adjustment Manual Zoom adjustment Digital Zoom ratio (Tele-to-Wide) 1:1.35 Internal sound system 16 W monaural Noise level 35 dB (Normal Power Consumption mode) 28 dB (ECO Power Consumption mode) Keystone correction angle Vertical: ± 5° Horizontal: ± 5° USB-B port compatibility USB 1.1 and 2.0 compliant for USB display or external mouse USB-A port compatibility One USB 1.1 and 2.0 compliant port for USB device input or EPSON document camera display	1	EPSON VS250 SVGA 3LCD Projector with Motorized screen	150,000	Maxell MC-EX-3051	149,600	149,600	ANS Associates, Lahore