

FINANCIAL COMPARATIVE STATEMENT								
ESTABLISHMENT OF GOVT: TECHNICAL & VOCATIONAL CENTRE (M/F) IN RENTED BUILDING & PROCUREMENT OF EQUIPMENT/MECHINERY & FURNITURE AT MADYEN, SWAT								
TENDER OPENING 28-04-2021								
(Computer LAB ITEMS)								
Item No.	Name of Items	Quantity	AURSOF PVT (Ltd), Peshawar		ANS Associates, Lahore		Lowest	Remarks
			Models	Financial Quoted Rates	Models	Financial Quoted Rates		
1	<p><b>Processor: 10th Generation Intel® Core™ i5-10400</b>, 12 MB Cache, 6 Core, 12 Threads, 2.9 GHz to 4.3 GHz.  Chipset: Intel B460 chipset or higher  Memory: 8GB - DDR4, 2666MHz  Hard Drive: 1TB 7200RPM 3.5" SATA HDD  Optical Drive: 9.5 mm Slimline DVD +/- RW  Graphics Card: Intel® UHD Graphics 630 with shared graphics memory or higher  Communication: Gigabit Ethernet controller 10/100/1000 (RJ45)  Ports: 2 USB 2.0(front), 2 USB 3.2 Gen 1 Type-A (front), 1 HDMI, 1 VGA  2 USB 3.2 Gen 1 Type-A (rear), 2 USB 2.0(rear), 1 RJ-45 Ethernet  Wireless: Intel® Wireless-AC 3165 802.11ac 1x1 + Bluetooth 4.2 or higher  Keyboard: USB Keyboard and Mouse  Antivirus with 1 year subscription  Display: 18.5" LED  Warranty: 3-years  Provision of Manufacturer / Distributor authorization letter in the name of undersigned is mandatory.</p>	25	Dell Optiplex 3080	118,800	Vestro 3888	105,931	105,931	ANS Associates, Lahore
2	<p><b>MULTIFUNCTIONAL PRINTERS</b>  Functions: PRINT/SCANNER/COPY/FAX</p>	1	HP Laserjet Pro M 227FDW	83,000	HP Laserjet Pro MFP M-227fdn Printer	81,600	81,600	ANS Associates, Lahore
3	<p><b>MULTIMEDIA PROJECTOR with motorized Screen system.</b>  Type of display Poly-silicon TFT active matrix  Resolution BrightLink 480i:  1024 × 768 pixels (XGA)  BrightLink 475Wi/485Wi:  1280 × 800 pixels (WXGA)  Lens F= 1.80  Focal length: 3.71 mm  Color reproduction Full color, 16.77 million colors  Brightness BrightLink 475Wi:  Normal Power Consumption mode:  White light output 2600 lumens (ISO 21118 standard)  Color light output 2600 lumens  ECO Power Consumption mode:  White light output 1800 lumens (ISO 21118 standard)  BrightLink 480i:  Normal Power Consumption mode:  White light output 3000 lumens (ISO 21118 standard)  Color light output 3000 lumens  ECO Power Consumption mode:  White light output 1800 lumens (ISO 21118 standard)  BrightLink 485Wi:  Normal Power Consumption mode: White light output 3100 lumens (ISO 21118 standard)  Color light output 3100 lumens  ECO Power Consumption mode:  White light output 1800 lumens (ISO 21118 standard)  Contrast ratio 3000 to 1 with Auto Iris on and Normal Power Consumption mode  Image size BrightLink 480i:  55.9 to 93.2 inches (1.42 to 2.37 m)  BrightLink 475Wi/485Wi:  60 to 100 inches (1.52 to 2.54 m)  Projection distance 13.7 to 23.5 inches (0.35 to 0.60 m)  Projection methods Front, wall or ceiling-mounted  Optical aspect ratio  (width-to-height) BrightLink 480i:  4:3  BrightLink 475Wi/485Wi:  16:10  Focus adjustment Manual  Zoom adjustment Digital  Zoom ratio  (Tele-to-Wide) 1:1.35  Internal sound system 16 W monaural  Noise level 35 dB (Normal Power Consumption mode)  28 dB (ECO Power Consumption mode)  Keystone correction angle Vertical: ± 5°  Horizontal: ± 5°  USB-B port compatibility USB 1.1 and 2.0 compliant for USB display or external mouse  USB-A port compatibility One USB 1.1 and 2.0 compliant port for USB device input or EPSON document camera</p>	1	EPSON VS250 SVGA 3LCD Projector with Motorized screen	150,000	Maxell MC-EX-3051	149,600	149,600	ANS Associates, Lahore